

جدول مشخصات مینی چیلر هپاکو

HEPACO

10.3 ~ 15.5 KW

model : HPCA...LD2	3	3.5	4.5	
Refrigerant				
Type	R22			
Cooling				
Cooling Capacity	Kw	10.3	12.5	15.5
COP		2.98	3.14	3.20
Sound Power	db(A)	72	73	73
Heating				
Heating capacity	Kw	-	-	-
COP		-	-	-
Compressor				
Quantity	n°	1	1	1
Type	Hermetic Scroll			
Minimum capacity step	%	0-100	0-100	0-100
Power input	Kw	3.44	3.97	4.78
Comp. total current	A	6.2	7.7	8.5
Fans				
Quantity	n°	1	2	2
Type	Axial fan			
User side exchanger				
Quantity	n°	1	1	1
Type	High Efficiency Brazed Plate Heat Exchanger			
Working water range temp.	°C	4-15		
Water flow rate	m ³ /h	26.6	31.7	39.3
Water Connection	inch	1	1 1/4	1 1/4
Pressure drop	kpa	3.6	11	10.8
Dimension and Weight				
Height	mm	970	1270	1270
Width	mm	990	990	990
Depth	mm	460	460	460
Weight	Kg	121	132	295
Electrical data				
power supply	v/ph/Hz	400/3~+N/50		

Scroll Air Cooled Mini Chiller

- Ambient air temperature 35 °C : User side exchanger inlet/outlet water temperature 12-7 °C
- Ambient air temperature 35 °C : Full load capacity steps 100%